

T12KM

Engine MITSUBISHI , S4L2-SD
Alternator MECC ALTE , ECO 28 1L/4

STANDARD FEATURES

- Mechanical governor
- Mechanically welded chassis with antivibration suspension
- Power circuit breaker
- Radiator for wiring T° of 50 °C [122 °F] max with mechanical fan
- Protective grille for fan and rotating parts
- 9dB(A) silencer supplied separately
- Charged DC starting battery with electrolyte
- 12 V charging alternator and starter
- Supplied with oil and coolant -30 °C
- User manual and commissioning guide



Voltage	Power ESP kWe/kVA	Power PRP kWe/kVA	Standby Amps	Dimensions	Weight
240MONO	12.0 / 12.0	10.9 / 10.9	50.0	Length: 1405mm [55in]	452kg [996 lbs] Net
230MONO	12.0 / 12.0	10.9 / 10.9	52.2	Width: 715mm [28in]	506kg [1116 lbs] Gross
220MONO	12.0 / 12.0	10.9 / 10.9	54.5	Height: 1053mm [41in]	



POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. A 10% overload capability is available for a period of 1 hour within 12-hour period of operation, in accordance with ISO 3046-1 –

ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERM OF USE

Standard reference conditions 25 °C Air Intlet Temp, 100 m A.S.L. 60 % relative humidity. All engine performance data based on the above mentioned maximum continuous ratings.

Type	dB(A)@1m	dB(A)@7m	Dimensions	Weight	Tank
 M126	70.7	60.7	Length: 1750mm [69in] Width: 715mm [28in] Height: 1230mm [48in]	600kg [1323lbs] Net 654kg [1442lbs] Gross	50 L
 M126-DW	70.7	60.7	Length: 1797mm [71in] Width: 775mm [31in] Height: 1391mm [55in]	679kg [1497lbs] Net 769kg [1695lbs] Gross	93 L



ENGINE SPECIFICATIONS

STANDARD FEATURES	Manufacturer / Model	MITSUBISHI S4L2-SD , 4-strokes, Athmo , [N/A] 4 X
	Cylinder Arrangement	L
	Displacement	1.75L [106.8C.I.]
	Bore and Stroke	78mm [3.1in.] X 92mm [3.6in.]
	Compression ratio	22 : 1
	Rated RPM	1500 Rpm
	Piston Speed	4.6m/s [15.1ft./s]
	Max. stand by Power at rated RPM	16.61kW [22BHP]
	Frequency regulation, steady state	+/- 2.5%
	BMEP	6.86bar [99psi]
Governor : type	MECA	
EXHAUST SYSTEM	Exhaust temperature	410°C [770°F]
	Exhaust gas flow	48.7L/s [103cfm]
	Max back pressure	700mm CE [28in. WG]
FUEL SYSTEM	110% (Stand By power)	[N/A]
	100% (of the Prime Power)	4.4L/h [1.2gal/hr]
	75% (of the Prime Power)	3.4L/h [0.9gal/hr]
	50% (of the Prime Power)	2.6L/h [0.7gal/hr]
	Max. fuel pump flow	18L/h [4.8gal/hr]
OIL SYSTEM	Total oil capacity w/filters	5.9L [1.6gal]
	Oil Pressure low idle	1bar [14.5psi]
	Oil Pressure rated RPM	4bar [58.0psi]
	Oil consumption 100% load	0.025L/h [0.007gal/hr]
	Oil capacity carter	5.4L [1.4gal]
THERMAL BALANCE	Heat rejection to exhaust	14kW [796Btu/mn]
	Radiated heat to ambient	2kW [114Btu/mn]
	Heat rejection to coolant	14kW [796Btu/mn]
AIR INTAKE	Max. intake restriction	200mm CE [8in. WG]
	Engine air flow	18.2L/s [39cfm]
COOLANT SYSTEM	Radiator & engine capacity	4.9L [1.3gal]
	Max water temperature	111 °C [232 °F]
	Outlet water temperature	93 °C [199 °F]
	Fan power	0.5 kW
	Fan air flow w/o restriction	0.8m ³ /s [1695cfm]
	Available restriction on air flow	10mm CE [0.4in. WG]
	Type of coolant	Gencool
	Thermostat	82-95 °C
EMISSIONS LEVEL	PM	100 mg/Nm ³
	CO	120 mg/Nm ³
	Nox	1350 mg/Nm ³
	HC	40 mg/Nm ³



ALTERNATOR SPECIFICATIONS

GENERAL DATAS	Manufacturer	MECC ALTE	
	Type	ECO 28 1L/4	
	Number of phase	1	
	Power factor (Cos Phi)	1	
	Altitude	1000	
	Overspeed	[N/A]	
	Pole : number	4	
	Exciter type	NO	
	Insulation : class, temperature rise	H / H	
	Voltage regulator	AVR	
	Total harmonics (TGH/THC)	[N/A]	
	Wave form : NEMA = TIF – TGH/THC	[N/A]	
	Wave form : CEI = FHT – TGH/THC	2	
	Bearing : number	1	
	Coupling	Direct	
	Voltage regulation 0 to 100% load	[N/A]	
	Recovery time (20% Volt dip) ms	[N/A]	
	SkVA with 90% of nominal sustained voltage (at 0.4PF)	N/A	
	OTHER DATAS	Continuous nominal rating @ 40 °C	13 kVA
		Standby rating @ 27 °C	13 kVA
Efficiencies @ 4/4 load		84.2 %	
Air flow		0.0883m ³ /s [187.10cfm]	
Short circuit ratio;50 (Kcc)		0.65	
Direct axis synchro reactance unsaturated (Xd)		175 %	
Quadra axis synchro reactance unsaturated (Xq)		76 %	
Open circuit time constant;50 (T'do)		0.87 ms	
Direct axis transient reactance saturated (X'd)		16.5 %	
Short circuit transient time constant (T'd)		0.045 ms	
Direct axis subtransient reactance saturated (X''d)		9.4 %	
Subtransient time constant (T''d)		0.015 ms	
Quadra axis subtransient reactance saturated (X''q)		21 %	
Zero sequence reactance unsaturated (Xo)		3.2 %	
Negative sequence reactance saturated (X2)		14.2 %	
Armature time constant (Ta)		0.013 ms	
No load excitation current (io)		[N/A]	
Full load excitation current (ic)		[N/A]	
Full load excitation voltage (uc)		[N/A]	
Recovery time (Delta U = 20% transitoire)		[N/A]	
Motor start (Delta = 20% perm. Or 50% trans.)	[N/A]		
Transient dip (4/4 charge) – PF : 1.8 AR	[N/A]		
No load losses	[N/A]		
Heat rejection	[N/A]		



CONTROL PANEL

Standard



NEXYS

Specifications :

Frequency meter, Ammeter, Voltmeter
Alarms and faults Oil pressure, water temperature,
Overcrank, Overspeed (>60 kVA), Min/max alternator,
Low fuel level, Emergency stop
Engine parameters Hours counter, Engine speed,
Battery voltage, Fuel level, Air preheating

Option



TELYS

Specifications :

Frequency meter, Ammeter, Voltmeter
Alarms and faults Oil pressure, water temperature, No
start-up, Overspeed, Min/max alternator, Min/max
battery voltage, Low fuel level, Emergency stop
Engine parameters Hours counter, Oil pressure, Water
temperature, Engine speed, Battery voltage, Fuel level

