



## XP-T8HKM-UK-ALIZE

### Product advantages

- ➔ Full control panel
- ➔ electric start
- ➔ Large Autonomy
- ➔ long life' engine
- ➔ Silent

### Miscellaneous

The top quality alliance of performance and soundproofing.



This product is QUALIGEN certified. Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After Sales Service) in order to provide the highest level of quality of our and thus to guarantee the users safety.

## XP-T8HKM-UK-ALIZE

### General specifications

Range	Industrial
Frequency (Hz)	50
Max. power (kW)	7.50
Max power. (kVA)	9.35
Nominal voltage (V)	230
Number of phase	Single phase - 230V
Acoustic pressure level Lw	94
Noise level dB(A) - 7m	68

### Engine specifications

Engine trademark	Mitsubishi
Engine type	L2E SDH
Distribution	Fuel
Start	Electrical
Fuel	Fuel
Autonomy (h)	19.2
Consumption (L/h)	2.6
Tank (L)	50
Oil Guard	Yes
Capacity (cm3)	635
Oil capacity (L)	2.4

### Alternator specifications

Type	Without collar or brush
Regulation	Mechanical
Protection class	IP 23
Insulation class	H

### Plugs and panels descriptive

1 x 2P+T 115V 16A - circuit breaker + 1 x 2P+T 230V 16A - circuit breaker + 1 x 2P+T 230V 32A - circuit breaker + Mics NEXYS

### Dimensions and weight

Length (cm)	150
Width (cm)	76
Height (cm)	103
Dry Weight (kgs)	340

### Packaging

Packaging type	Canopy + Film
Length (cm)	150
Width (cm)	76
Height (cm)	103

