



ST 2.36 H

Product advantages

- Excellent performance/price ratio
- Helix in graphite cast iron
- Mechanic seal in ceramic carbon
- OHV Honda professional engine
- Oil level safety

Miscellaneous

Water pumps suitable for clear water which little sediment.



ST 2.36 H

General specifications

Range	Open Aqualine
-------	---------------

Water pumps specifications

Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (L/min)	600
Outflow maximum (m ³ /h)	36
Lifting height (m)	29
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes

Engine specifications

Engine trademark	Honda
Engine type	GX 120
Distribution	S.V.
Start	Launcher
Fuel	Petrol (unlead)
Autonomy (h)	2
Consumption (L/h)	1
Tank (L)	2
Oil Guard	Yes
HP 3600 tr/mn max.	3.5
Capacity (cm ³)	118
Oil capacity (L)	0.6

Delivered accessories

Inlet filter
Circlips
Screw-on connectors

Dimensions and weight

Length (cm)	46.8
Width (cm)	36.2
Height (cm)	38
Dry Weight (kgs)	23

Packaging

Packaging type	Box
Length (cm)	48.5
Width (cm)	38.5
Height (cm)	40
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	150

Options

--