



ST 3.60 H

Product advantages

- Excellent performance/price ratio
- Helix in graphite cast iron
- Mechanic seal in ceramic carbon
- OHV Honda professional engine
- Oil level safety

Miscellaneous

For frequent use, heavy duty professional applications.



ST 3.60 H

General specifications

Range	Intens Aqualine
-------	-----------------

Water pumps specifications

Suction diameter [mm]	80
Backflow diameter (mm)	80
Outflow maximum (L/min)	970
Outflow maximum (m3/h)	54
Lifting height (m)	26
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes

Engine specifications

Engine trademark	Honda
Engine type	GX 160
Distribution	S.V.
Start	Launcher
Fuel	Petrol (unlead)
Autonomy (h)	3.4
Consumption (L/h)	0.9
Tank (L)	3.1
Oil Guard	Yes
HP 3600 tr/mn max.	4.8
Capacity (cm3)	163
Oil capacity (L)	0.6

Delivered accessories

Inlet filter
Circlips
Screw-on connectors

Dimensions and weight

Length (cm)	50.5
Width (cm)	41.4
Height (cm)	44.8
Dry Weight (kgs)	29

Packaging

Packaging type	Box
Length (cm)	52
Width (cm)	42.5
Height (cm)	46.5
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	155



ST 3.60 H

Options

--