




## TR 3.60 H

### Product advantages

- Easy access to the turbine
- OHV Honda professional engine
- Oil level safety
- Helix and impeller in graphic cast iron
- Mechanic seal in ceramic carbon

### Miscellaneous

For frequent use, heavy duty professional applications.



## TR 3.60 H

### General specifications

Range	Intens Aqualine
-------	-----------------

### Water pumps specifications

Suction diameter [mm]	80
Backflow diameter (mm)	80
Outflow maximum (L/min)	900
Outflow maximum (m <sup>3</sup> /h)	54
Lifting height (m)	26
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes

### Engine specifications

Engine trademark	Honda
Engine type	GX 160
Distribution	O.H.V.
Start	Launcher
Fuel	Petrol (unlead)
Autonomy (h)	3.4
Consumption (L/h)	0.9
Tank (L)	3.1
Oil Guard	Yes
HP 3600 tr/mn max.	4.8
Capacity (cm <sup>3</sup> )	163
Oil capacity (L)	0.6

### Delivered accessories

Inlet filter
Circlips
Screw-on connectors

### Dimensions and weight

Length (cm)	50.5
Width (cm)	39.8
Height (cm)	46.6
Dry Weight (kgs)	29

### Packaging

Packaging type	Box
Length (cm)	51.5
Width (cm)	42
Height (cm)	48
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	155

Options


--