

J275K - Generating set

JOHN DEERE, 6081HF001 LEROY SOMER LSA462L6-SH-F12

J275K Power Products Generating set, equipped with a JOHN DEERE engine and LEROY SOMER alternator.

General characteristics

Mechanic governor

Mechanically welded chassis with antivibration suspension

Main line circuit breaker

Radiator for wiring temperature of 48/50°C max with mechanical fan

Protective grille for fan and rotating parts

9 dB(A) silencer supplied separately

Charger DC starting battery with electrolyte

12 V charge alternator and starter

Delivered with oil and coolant -30°C

Manual for use and installation



| Voltage (V) | ESP Power (kWe/kVA) | PRP Power (kWe/kVA) | Back-up power (A) | Dimensions (L. x l. x h.) | Weight |
|-------------|---------------------|---------------------|-------------------|------------------------------|---------------|
| 415/240 | 211.2/264 | 211.2/264 | 367 | | |
| 400/230 | 220/275 | 220/275 | 396 | | |
| 380/220 | 220/275 | 220/275 | 417 | Length: 2900 mm | 2170 kg net |
| 200/115 | 220/275 | 220/275 | 793 | Width: 1300 mm | 2570 kg gross |
| 240 TRI | 211.2/264 | 211.2/264 | 635 | Height: 1697 mm | |
| 230 TRI | 220/275 | 220/275 | 690 | | |
| 220 TRI | 220/275 | 220/275 | 721 | | |

Hoods

| _ | Model | dB(A)@1m | dB(A)@7m | Dimensions (L. x l. x h.) | Weight | Tank |
|----------------|-----------|----------|----------|---|------------------------------|--------|
| Image: M227-DV | M227-DW48 | 80 | 80 | Length: 4056mm Width: 1380mm Height: 2618mm | 4200 kg net 6222 kg gross | 2130 L |
| Dishe. | M227 | 80 | 80 | Length: 4004mm Width:1380mm Height: 2145mm | 3150 kg net 3560 kg gross | 390 L |

Standard Control Panel

NEXYS



The NEXYS is a versatile control unit allowing operation in manual or automatic mode. Equipped with an LCD screen, the user-friendly NEXYS offers high-quality basic functions to guarantee simple, reliable operation of your generating set.

Offers the following functions:

Standard electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, engine speed, battery voltage, fuel level.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed (> 60 kVA), charging alternator fault, low fuel level, emergency stop.

For more information, please refer to the sales documentation.

Optional control panel

TELYS



The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

Ergonomics: wheel for navigating around the various menus.

Communication: remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.