

## J44K - Generating set

J44K Power Products Generating set, equipped with a JOHN DEERE engine and MECC ALTE alternator.



### General characteristics

Mechanic governor
Mechanically welded chassis with antivibration suspension
Main line circuit breaker
Radiator for wiring temperature of 48/50°C max with mechanical fan
Protective grille for fan and rotating parts
9 dB(A) silencer supplied separately
Charger DC starting battery with electrolyte
12 V charge alternator and starter
Delivered with oil and coolant -30°C
Manual for use and installation



Voltage (V)	ESP Power (kWe/kVA)	PRP Power (kWe/kVA)	Back-up power (A)	Dimensions (L. x l. x h.)	Weight
415/240	35.2/44	35.2/44	61	Length : 1700 mm Width : 896 mm Height : 1221 mm	820 kg net 930 kg gross
400/230	35.2/44	35.2/44	63		
380/220	35.2/44	35.2/44	66		
200/115	35.2/44	35.2/44	127		
240 TRI	35.2/44	35.2/44	105		
230 TRI	35.2/44	35.2/44	110		
220 TRI	35.2/44	35.2/44	115		
220/127	28/35	28/35	91		

## Hoods

	Model	dB(A)@1m	dB(A)@7m	Dimensions (L. x l. x h.)	Weight	Tank
	M127-DW48	73	73	<b>Length :</b> 2160mm <b>Width :</b> 966mm <b>Height :</b> 1631mm	1215 kg net 1612 kg gross	420 L
	M127	73	73	<b>Length :</b> 2080mm <b>Width :</b> 960mm <b>Height :</b> 1415mm	1040 kg net 1150 kg gross	100 L

### Standard Control Panel

### NEXYS



The NEXYS is a versatile control unit allowing operation in manual or automatic mode. Equipped with an LCD screen, the user-friendly NEXYS offers high-quality basic functions to guarantee simple, reliable operation of your generating set.

Offers the following functions:

**Standard electrical measurements:** voltmeter, frequency meter, ammeter.

**Engine parameters:** working hours counter, engine speed, battery voltage, fuel level.

**Alarms and faults:** oil pressure, coolant temperature, failure to start, overspeed (> 60 kVA), charging alternator fault, low fuel level, emergency stop.

For more information, please refer to the sales documentation.

### Optional control panel

### TELYS



The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

**Electrical measurements:** voltmeter, frequency meter, ammeter.

**Engine parameters:** working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

**Alarms and faults:** oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

**Ergonomics:** wheel for navigating around the various menus.

**Communication:** remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.