

T33K - Generating set

MITSUBISHI, S4S-SD MECC ALTE ECO28VL-F12

T33K Power Products Generating set, equipped with a MITSUBISHI engine and MECC ALTE alternator.

General characteristics

Mechanic governor

Mechanically welded chassis with antivibration suspension

Main line circuit breaker

Radiator for wiring temperature of 48/50°C max with mechanical fan

Protective grille for fan and rotating parts

9 dB(A) silencer supplied separately

Charger DC starting battery with electrolyte

12 V charge alternator and starter

Delivered with oil and coolant -30°C

Manual for use and installation



Voltage (V)	ESP Power (kWe/kVA)	PRP Power (kWe/kVA)	Back-up power (A)	Dimensions (L. x l. x h.)	Weight
415/240	24.8/31	24.8/31	43	Length : 1700 mm Width : 896 mm Height : 1144 mm	660 kg net 760 kg gross
400/230	26.4/33	26.4/33	47		
380/220	26.4/33	26.4/33	50		
200/115	26.4/33	26.4/33	95		
240 TRI	26.4/33	26.4/33	79		
230 TRI	26.4/33	26.4/33	82		
220 TRI	26.4/33	26.4/33	86		

Hoods

Model	dB(A)@1m	dB(A)@7m	Dimensions (L. x l. x h.)	Weight	Tank
M127	73	73	Length: 2080mm Width: 960mm Height: 1415mm	890 kg net 990 kg gross	100 L

Standard Control Panel

NEXYS



The NEXYS is a versatile control unit allowing operation in manual or automatic mode. Equipped with an LCD screen, the user-friendly NEXYS offers high-quality basic functions to guarantee simple, reliable operation of your generating set.

Offers the following functions:

Standard electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, engine speed, battery voltage, fuel level.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed (> 60 kVA), charging alternator fault, low fuel level, emergency stop.

For more information, please refer to the sales documentation.

Optional control panel

TELYS



The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

Ergonomics: wheel for navigating around the various menus.

Communication: remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.