



HP 2.26 H

Product advantages

- Automatic priming
- Mechanic seal in ceramic
- Helix and impeller in graphic cast iron

Miscellaneous

Increased technicity for specific applications.



HP 2.26 H

General specifications

Range	170_Specialist_Aqua
-------	---------------------

Water pumps specifications

Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (L/min)	440
Outflow maximum (m3/h)	26.4
Lifting height (m)	57
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes

Engine specifications

Engine trademark	Honda
Engine type	GX 160
Distribution	O.H.V.
Start	Launcher
Fuel	Petrol (unlead)
Autonomy (h)	3.4
Consumption (L/h)	0.9
Tank (L)	3.1
Oil Guard	Yes
HP 3600 tr/mn max.	4.8
Capacity (cm3)	163
Oil capacity (L)	0.6

Delivered accessories

Inlet filter
Circlips
Screw-on connectors

Dimensions and weight

Length (cm)	41.5
Width (cm)	54.5
Height (cm)	45.5
Dry Weight (kgs)	30

Packaging

Packaging type	Box
Length (cm)	54
Width (cm)	42
Height (cm)	45
Pallet type	120/80
Number of box by pallet	12

Options

--