



XC 2.34 H

Product advantages

- Automatic priming
- reduced consumption
- Mechanic seal in ceramic carbon
- Rivets and bolts of the pump body in

Zoom

Automatic priming. PET pump body, chamber and impeller. Mechanical seal in ceramic carbon. Stainless steel fixing on pump body

Miscellaneous

Increased technicity for specific applications.



XC 2.34 H

General specifications

Range	170_Specialist_Aqua
-------	---------------------

Water pumps specifications

Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (L/min)	560
Outflow maximum (m3/h)	33.6
Lifting height (m)	26
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes

Engine specifications

Engine trademark	Honda
Engine type	GX 120
Distribution	O.H.V.
Start	Launcher
Fuel	Petrol (unlead)
Autonomy (h)	2
Consumption (L/h)	1
Tank (L)	2
Oil Guard	Yes
HP 3600 tr/mn max.	3.5
Capacity (cm3)	118
Oil capacity (L)	0.6

Delivered accessories

Inlet filter
Circlips
Screw-on connectors

Dimensions and weight

Length (cm)	52
Width (cm)	42.8
Height (cm)	44.8
Dry Weight (kgs)	22

Packaging

Packaging type	Box
Length (cm)	51
Width (cm)	43
Height (cm)	44
Pallet type	120/80
Number of box by pallet	12



XC 2.34 H

Options

--