

TECHNIC 3000 UK

PORTABLE POWER

50Hz range Technic

Product advantages

- Solid and compact frame
- Large autonomy
- ➡ Kohler Professional Engine warranty 3 years

Divers

Exceptional long run time suited to professional working conditions.











This product is QUALIGEN certified. Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After Sales Service) in order to provide the highest level of quality of our and thus to guarantee the users safety.

TECHNIC 3000 UK

General specifications

Technic
50
3
3.75
230
Single phase - 230V
96
83
73

Engine specifications

For all a constant and a	IZ - l-1
Engine trademark	Kohler
Engine type	CH 270
Distribution	O.H.V.
Start	Launcher
Fuel	Petrol (unlead)
Autonomy (h)	10
Comsumption (L/h]	1.3
Tank (L)	13
Oil Guard	Yes
Capacity (cm3)	208
Oil capacity (L)	0.6

Alternator specifications

Туре	Without collar or brush
Regulation	Mechanical
Protection class	IP 23
Insulation class	Н

Plugs and panel descriptive

1 x 2P+T 115V 16A – circuit breaker + 1 x 2P+T 230V 16A $\,$ – circuit breaker + hours counter

Dimensions and weight

Lenght (cm)	65
Width (cm)	51
Height (cm)	46
Dry Weight (kgs)	43

Packaging

Packaging type	Box
Length (cm)	66
Width (cm)	52.5
Height (cm)	47
Pallet type	140/110
Number of box by pallet	12
Pallet height (cm)	150



TECHNIC 3000 UK

Options



R01	Differential box	This set includes the hour meter and the differential circuit breaker.
R05M	Manual changeover switch	The manual changeover switch is used to connect and disconnect a generating set manually to a domestic circuit when there is a power cut.
RKB1	Trolley kit	Trolley kit for generating sets less or equal to 6 kW
RHO	Cover	Cover for SDMO generator sets and petrol or diesel driven pumps
RPM	Male plugs	Male plugs 16A blue 230V male plug, 16A yellow 230V male plug
RPQ	Earth spike	For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable.